

STODDARD SOLVENT MS 66 1%
AROM 547108

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Ashland	Regulatory Information Number	1-800-325-3751
P.O. Box 2219	Telephone	614-790-3333
Columbus, OH 43216	Emergency telephone number	1-800-ASHLAND (1-800-274-5263)

Product name	STODDARD SOLVENT MS 66 1% AROM
Product code	547108
Product Use Description	No data

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid, hydrocarbon-like, colourless

WARNING! Combustible Liquid, Mild skin, Mild eye.

Potential Health Effects

Routes of Exposure

Inhalation, Skin contact, Eye Contact

Eye Contact

May cause mild eye irritation. Symptoms include stinging, tearing, and redness.

Skin Contact

May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin, and skin burns. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

Inhalation

STODDARD SOLVENT MS 66 1%
AROM 547108

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions)

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other central nervous system effects

Target Organs

Exposure to this material (or a component) has been found to cause kidney damage in male rats. The mechanism by which this toxicity occurs is specific to the male rat and the kidney effects are not expected to occur in humans.

Carcinogenicity

Based on the available information, this material cannot be classified with regard to carcinogenicity. This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA).

Reproductive Hazard

No data

Other Information

No data

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Concentration
SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPHATIC	64742-88-7	<=100%

4. FIRST AID MEASURES

STODDARD SOLVENT MS 66 1%
AROM 547108

Eyes

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

Notes to Physician

Hazards: This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

foam, carbon dioxide (CO₂), dry chemical

Hazardous Combustion Products

May form:, carbon dioxide and carbon monoxide, various hydrocarbons

Precautions for Fire-Fighting

If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

STODDARD SOLVENT MS 66 1%
AROM 547108

Flammability Class for Flammable Liquids
Combustible Liquid Class IIIA

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

For personal protection see section 8. Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source. Prevent from entering drains, sewers, streams or other bodies of water. Prevent from spreading. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

Environmental Precautions

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

Methods for Cleaning Up

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.

Storage

No data

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

General Advice

STODDARD SOLVENT MS 66 1%
AROM 547108

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Eye Protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

Skin and Body Protection

Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

Respiratory Protection

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH-approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Form	No data
Colour	colourless, clear
Odour	hydrocarbon-like
Boiling point/range	315.00 °F / 157.22 °C
pH	No data
Flash point	104.99 °F / 40.55 °C Tag closed cup
Evaporation rate	0.11 N-Butyl Acetate
Explosion limits	1.0 %(V) 6.0 %(V)
Vapour pressure	2 mmHg @ 68.00 °F / 20.00 °C
Vapour density	4.9
Density	0.7720 g/cm ³ @ 60.00 °F / 15.56 °C 6.44 lb/gal @ 60.00 °F / 15.56 °C

STODDARD SOLVENT MS 66 1%
AROM 547108

Solubility	No data
Partition coefficient (n-octanol/water)	No data
Autoignition temperature	500.0 °F / 260.0 °C

10. STABILITY AND REACTIVITY

Stability

Stable.

Conditions to Avoid

Avoid contact with:

Incompatible Products

Avoid contact with:, strong oxidizing agents

Hazardous Decomposition Products

May form:, carbon dioxide and carbon monoxide, various hydrocarbons

Hazardous Reactions

Product will not undergo hazardous polymerization.

Thermal Decomposition

No data

11. TOXICOLOGICAL INFORMATION

Acute Oral Toxicity

SOLVENT NAPHTHA (PETROLEUM), LD 50 Rat: 5,000 mg/kg
MEDIUM ALIPHATIC

Acute Inhalation Toxicity

SOLVENT NAPHTHA (PETROLEUM), LC 50 Rat: 5500 ppm, 4 h
MEDIUM ALIPHATIC

Acute Dermal Toxicity

SOLVENT NAPHTHA (PETROLEUM), LD 50 Rabbit: 3,000 mg/kg
MEDIUM ALIPHATIC

STODDARD SOLVENT MS 66 1%
AROM 547108

12. ECOLOGICAL INFORMATION

Aquatic Toxicity

Acute and Prolonged Toxicity to Fish

No data

Acute Toxicity to Aquatic Invertebrates

No data

Environmental Fate and Pathways

No data

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

Dispose of in accordance with all applicable local, state and federal regulations. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION

IMDG:

UN1268, PETROLEUM DISTILLATES, N.O.S. (ALIPHATIC PETROLEUM DISTILLATES,) 3, III

IATA_P:

UN1268, Petroleum distillates, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES,) 3, III

IATA_C:

UN1268, Petroleum distillates, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES,) 3, III

CFR_ROAD:

UN1268, Petroleum distillates, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES,) 3, III

CFR_RAIL:

UN1268, Petroleum distillates, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES,) 3, III

STODDARD SOLVENT MS 66 1%
AROM 547108

CFR_INWTR:

UN1268, Petroleum distillates, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES,) 3, III

IMDG_INWTR:

UN1268, PETROLEUM DISTILLATES, N.O.S. (ALIPHATIC PETROLEUM DISTILLATES,) 3, III

IMDG_ROAD:

UN1268, PETROLEUM DISTILLATES, N.O.S. (ALIPHATIC PETROLEUM DISTILLATES,) 3, III

IMDG_RAIL:

UN1268, PETROLEUM DISTILLATES, N.O.S. (ALIPHATIC PETROLEUM DISTILLATES,) 3, III

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

15. REGULATORY INFORMATION

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects or any other harm.

Additional Regulations

US. OSHA Hazard Communication Standard: On One of the Floor Lists of the OSHA HCS (29 CFR 1910.1200).

US. High Production Volume Chemicals

US. TSCA IUR 2006, Partially Exempt Petroleum Process Streams (40 CFR 710.46(b)(1))

OECD. Program to investigate the potential hazards of high production volume further work.

SARA 313 Component(s)

OSHA Hazards

Combustible Liquid
Mild skin
Mild eye

HMIS

Health

Flammability

Reactivity

Other

No data

ASHLAND
SAFETY DATA SHEET

Page: 9
Revision Date: 04/09/2007
Print Date: 9/19/2007
MSDS Number: R0197908
Version: 1.4

STODDARD SOLVENT MS 66 1%
AROM 547108

NFPA 0 2 0

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).