

**** MATERIAL SAFETY DATA SHEET ****

28202 ISO HEET Gas Line Antifreeze

SEC 1 - PRODUCT AND MANUFACTURER INFO	SEC 9 - PHYS, CHEM PROPERTIES
SEC 2 - COMPOSITION INFORMATION	SEC 10 - STABILITY, REACTIVITY
SEC 3 - HAZARDS IDENTIFICATION	SEC 11 - TOXICOLOGY INFORMATION
SEC 4 - FIRST AID MEASURES	SEC 12 - ECOLOGICAL INFORMATION
SEC 5 - FIRE FIGHTING MEASURES	SEC 13 - DISPOSAL
CONSIDERATIONS	
SEC 6 - ACCIDENTAL RELEASE MEASURES	SEC 14 - TRANSPORT INFORMATION
SEC 7 - HANDLING AND STORAGE	SEC 15 - REGULATORY INFORMATION
SEC 8 - EXPOSURE, PERS. PROTECTION	SEC 16 - ADDITIONAL INFORMATION

**** SECTION 1 - CHEMICAL PRODUCT AND MANUFACTURER IDENTIFICATION ****

Product Name: 28202 ISO HEET Gas Line Antifreeze

Part Number:

28202

Product CAS: (None)

Product Code: 28202

Synonyms: 28202 ISO HEET Gas Line Antifreeze

MANUFACTURER IDENTIFICATION

Name: Gold Eagle Company

Address: 4400 S. Kildare Blvd.

City: Chicago **State:** IL **Zip:** 60632-4372

For information call: 773-376-4400

Emergency Number: N/A

Emergency Agency: INFOTRAC

Agency Number: 1-800-535-5053

MSDS Effective Date: 8/5/2005

MSDS Supersedes Date: 3/31/2006

Miscellaneous:

Product CAS: Mixture

Chemical Name: Isopropanol

Brief Description: Gas line antifreeze for automobiles.

[Return to top](#)

**** SECTION 2 - COMPOSITION, INFORMATION ON INGREDIENTS ****

Chemical Name	CAS	MIN
MAX		
Isopropanol	67-63-0	99
99		
Proprietary Additive	(none)	1
1		
Miscellaneous:		
CHEMICAL NAME	LIMIT VALUES	
Isopropanol	PEL 400 ppm	
	PEL 980 mg/m3	
Proprietary Additive (CAS#=Mixture)	N/A	
Return to top		

**** SECTION 3 - HAZARDS IDENTIFICATION ****

EMERGENCY OVERVIEW:

NFPA: Health: 2 Fire: 3 Reactivity: 0 Specific Hazard: None

HMIS: Health: 2 Flammability: 3 Reactivity: 0 PPE: B

Miscellaneous:

This product does not contain any components above de minimus concentrations that are considered carcinogenic by OSHA, IARC or NTP.

POTENTIAL HEALTH EFFECTS

Target Organs/Primary Route(s) of Entry:

Eye:

Irritant.

Skin:

Prolonged or repeated skin contact may cause dermatitis, scaling and possible systemic effects.

Ingestion:

Low level of toxicity, small amounts of liquid aspirated into the respiratory system during ingestion may cause pulmonary edema.

Inhalation:

Narcotic chemical affecting central nervous system resulting in: dizziness, nausea, visual impairment, narcosis and muscular impairment.

Miscellaneous:

[Return to top](#)

****** SECTION 4 - FIRST AID MEASURES ******

Eye:

If the product contacts the eyes, immediately wash the eyes with large quantities of room temperature water for at least 15 minutes, occasionally lifting the lower and upper lids. Get medical attention immediately. A follow up visit to an ophthalmologist should be made. Contact lenses should not be worn when working with this chemical.

Skin:

If the product contacts the skin, promptly wash the contaminated skin with soap and water for at least 15 minutes. If this product penetrates the clothing, promptly remove the clothing and wash the skin with soap and water. Systemic effects may be delayed 18 to 72 hours, therefore keep individual under observation.

Ingestion:

If this product is ingested. DO NOT INDUCE A PERSON TO VOMIT. Get medical attention immediately.

Inhalation:

Move the exposed person to fresh air at once and call emergency medical care. If breathing has stopped, give artificial respiration. If breathing is difficult, give humidified oxygen.

Notes to Physician:

No data available.

[Return to top](#)

****** SECTION 5 - FIRE FIGHTING MEASURES ******

Flash Point: 54 F. (12.2 C.) TOC

AutoIgnition Temperature: N/A

Flammable Limits

Lower Limit: Explosive Limit (LEL): 2.0

Upper Limit: Explosive Limit (UEL): 12.0

Extinguishing Media:

Use halon replacement or carbon dioxide extinguishers or alcohol foam for small fires. Water spray or fog can cool fire but may not be effective in extinguishing fire. Large fires should be extinguished with alcohol foam. Use water spray to cool containers exposed to fire. Containers may explode in heat or fire.

Unusual Fire and Explosion Hazards:

Dangerous fire and explosion hazard when exposed to heat or flame. Isopropanol is extremely flammable and forms explosive mixtures with air. Isopropanol vapors may travel considerable distance to a source of ignition and flash back.

Special Fire Fighting Procedures:

Wear NIOSH approved SCBA respirator in the positive pressure mode and chemical protective clothing.

General Information:

Flammable Limits: 2.0 to 12.0

[Return to top](#)

****** SECTION 6 - ACCIDENTAL RELEASE MEASURES ******

Small Spill: Remove sources of heat or ignition, provide adequate ventilation, contain leak using absorbent, inert, non-combustible material.

Large Spill: Contain spill, transfer to secure containers. In the event of an uncontrolled material release, the user should determine if release is

reportable
under applicable laws and regulations.
[Return to top](#)

****** SECTION 7 - HANDLING AND STORAGE ******

Handling:

See other sections of MSDS.

Storage:

See other sections of MSDS.

[Return to top](#)

****** SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION ******

GENERAL HYGIENE CONSIDERATIONS:

Use normal hygiene practices.

OTHER PRECAUTIONS:

Product is flammable, handle accordingly.

ENGINEERING CONTROLS:

Local Exhaust: Provide local ventilation to maintain exposure levels below recommended exposure limits.

Mechanical (General): In confined spaces, mechanical ventilation may be required.

Special Ventilation: Review Permissible Exposure Level (PEL's).

Other Ventilation: N/A

PERSONAL PROTECTIVE EQUIPMENT

Eyes/face:

Use splash proof chemical, safety goggles or appropriate full-face respirator.
Contact lenses should not be worn when working with this chemical.

Skin:

Use natural rubber or neoprene gloves as required.

Respirators:

Do not use air purifying respirator. Use NIOSH approved respirator approved supplied or self contained respirator. Respirators must be selected

based on the airborne levels found in the workplace and must not exceed the working limits of the respirator.

Other Protective Clothing/Equipment:

If there is a possibility of exposure of an individual's body to the product, wear body covering work clothes to avoid prolonged or repeated exposure.

[Return to top](#)

****** SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES ******

Appearance/Odor:

Water white liquid, solvent odor
pH: N/A

Vapor Pressure: (MM HG): 97.0

Vapor Density (Air=1): GT 1.0

Evaporation Rate: N/A

Viscosity: N/A

Boiling Point: 180 F. (82.2 C.)

Freezing/Melting Point: N/A

Decomposition Temperature: N/A

Solubility in Water: Soluble

Specific Gravity: 0.787

Molecular Formula: N/A

Molecular Weight: N/A

VOC Coating (minus water): 0 Lbs/Gallon

Coating Density : 0 Lbs/Gallon

Solvent Density : 0 Lbs/Gallon

Percent Solvent (volume): 0

Percent Solids (volume): 0

Percent Water (volume): 0

Percent Volatile by Weight: 0

Miscellaneous:

% Volatile/Volume: 100.0

Specific Gravity (H2O = 1): N/A

Percent Solvent (Volume): N/A

Percent Solids (Volume): N/A

Percent Water (Volume): N/A

Product is flammable, keep away from sources of ignition, combustibles, oxidizing material and acid. Store in an area equipped with automatic sprinklers or fire extinguishing system. Empty containers contain product residues, assume empty container to have the same hazards as full containers.

[Return to top](#)

****** SECTION 10 - STABILITY AND REACTIVITY ******

Chemical Stability:

Stable: Yes

Conditions to Avoid:

Store in a well ventilated place away from sources of ignition, combustibles, oxidizing materials and acid.

Incompatibilities with Other Materials:

Strong oxidizing agents, amines, chlorinated compounds and caustic materials.

Hazardous Decomposition Products:

Excessive heating and/or incomplete combustion will produce carbon monoxide.

Hazardous Polymerization:

Hazardous Polymerization May Occur: No

[Return to top](#)

****** SECTION 11 - TOXICOLOGICAL INFORMATION ******

No data available.

[Return to top](#)

****** SECTION 12 - ECOLOGICAL INFORMATION ******

No data available.

[Return to top](#)

****** SECTION 13 - DISPOSAL CONSIDERATIONS ******

Dispose of product in accordance with local, state, and federal regulations. Before attempting clean up, refer to other sections of MSDS for hazard warning information.

[Return to top](#)

****** SECTION 14 - TRANSPORT INFORMATION ******

Transportation Information:

Shipping Information (CFR 49 and IMDG):

Proper Shipping Name: Alcohol, antifreeze

DOT Hazard Class: Consumer commodity, ORM-D

DOT UN Number: None required.

IMDG Shipping Name: Dangerous Goods in Limited Quantities of Class 3.2 (Isopropanol), PGII

Label Information:

No data available.

[Return to top](#)

****** SECTION 15 - REGULATORY INFORMATION ******

SARA Title III:

Section 302: None
Section 304: None
Section 311: Hazard categories-Fire Hazard-Yes; Acute=Yes and
Chronic=Yes
Section 313: None

CERCLA:

Section 311(b)(4): Requires discharges of crude oil and petroleum products in any kind or form to waters must immediately be reported to the National Response Center at (800) 424-8802.

[Return to top](#)

****** SECTION 16 - ADDITIONAL INFORMATION ******

Disclaimer: Information presented herein is believed to be factual, as it has been derived from the works and opinions of persons believed to be qualified experts. However, nothing contained in this information is to be taken as warranty or representation for which the Gold Eagle Co. bears legal responsibility. The user should review any recommendations in the specific context of the intended use to determine whether they are appropriate.

Prepared by: Mike Profetto

[Return to top](#)